

Shenzhen Enster Electronics Co.,LTD

100-500m Long Distance Tower Crane 30X Optical Zoom
Camera



30X Tower Crane Zoom Camera

30X Optical Zoom

4.7-141mm Auto Focus Lens

| | | |
|-------------------|------------------|---|
| | | IPH5902-A30 |
| Camera Type | | Long Distance |
| System | | Embedded |
| Camera | Effective Pixels | 2.0 Mega Pixels |
| | | Main stream:2592*1520 |
| | | Sub stream:704*576 |
| | Frames Rates | 1980*1080@30/25fps |
| | Image Sensor | 1/2.9" Sony CMOS Sensor with ICR |
| | | 2.0 megapixel resolution (1945H*1097V) |
| | DSP | Dual core 32-bit DSP |
| | | HI3516C |
| Min. Illumination | Color | 0.001Lux@F1.2 |
| | B/W | 0.0001 Lux@F1.2 |
| Adjust Parameters | DWDR,BLC,D | |
| Video | Compression | H.264 Main profile |
| | Stream | support dual stream,AVI format |
| | Bit Rate | support 0.1M ~8Mbps bit rate adjustable |
| | Frame Rates | support 1~30fps adjust |
| Audio | Input and output | 1ch input(microphone),1 |
| | Compression | G.711 compression,support two-way aud |
| Alarm | Types | Motion De |

| | | |
|---------|----------------------|---|
| Network | WEB Browser | Support WEB remote con |
| | Smart Phone | mobile remot |
| | CMS Software | Uniform CMS Software(|
| | Cloud P2P | www.enster.com , MYE |
| | Network | 10/100M,Support RT |
| | ONVIF | |
| General | Language | 20 kinds of languages such as English, Finnish, F Spanish, Thai, |
| | IR Cut Filter | Set of do |
| | Lens Mount | Autofocus Lens 4.7-141mm |
| | View Distance | |
| | Waterproof Criterion | |
| | I/O Connector | 1*DC Conn |
| | Supplied Voltage | DC |
| | Power Consumption | IR On: 600m |
| | Working Environment | -10 ° Built in Heater being optional adde |
| | Weight | |